IQ Trading
м.Київ, Україна, вул. Межигірська,87-А
+38(044)351-14-37, www.iqtrading.com.ua



AT-SBx8106

Код: AT-SBx8106

Розничная стоимость: 214 489,44 грн
5 808,00 usd

Allied Telesis SwitchBlade x8100 Series Advanced Layer 3+ chassis switches є розроблений для розрізнення високої продуктивності, безперервно. Два control card options, CFC400 і CFC960, надають solutions for medium and large networks. Потужність до постачання двох chassis при використанні CFC960 забезпечує потужну і повноцінну мережеву важливу технологію вирішення, яка може навіть бути розповсюджена над довгою відстанню.
SwitchBlade x8100 an extensive range of connectivity options. Двома керуванням карток є уповноваженим з чотирма або лінією ліхтаря літери в 6 або 12 слот chassis. Gigabit and 10 Gigabit line card options ensure a system capable of meeting the requirements of today's networks, and the flexibility to expand when required. Active-Active switching fabric utilizes all available time, and fast failover is provided with the second control card in hot-standby. The SwitchBlade's highly resilient design включають dual controllers, dual PSUs і dual redundant passive backplane paths. Спроможність до hot-swap additional control cards, line cards і system or PoE power supplies guarantees maximum system uptime. The SwitchBlade x8100 Series ensures online resources and applications are always available.
The SwitchBlade x8100 Series is incredibly eco-friendly, використовуючи high-efficiency power supplies and low-power chip sets. Easily the most power efficient chassis в його class, the SwitchBlade x8100 Series features lower cost of ownership — and is better for the planet, too.

Характеристики

Количество портов	24
Скорость портов	1 Гбит/с, 10 Гбит/с
Функционал	Уровень 3 Plus
Наличие SFP портов	Присутствует
Возможность питание PoE устройств	IEEE 802.3at (До 30 Вт)
Количество PoE портов	24
Тип устройства	Коммутаторы в виде модульного шасси
Тип источника питания	Два внутр.
Опционально: -48 В пост.тока	Поддерживает
Дополнительный источник питания	AT-SBxPWRPOE1, AT-SBxPWRSYS1
Максимальная мощность PoE	2400 Вт
Веб-интерфейс	Поддерживает
CLI/Telnet/SNMP	Поддерживает
AMF	Поддерживает
EPSRing	Поддерживает
VLAN на основе IEEE802.1Q	4096
Ш x Г x В мм	48 x 39 x 17,6 см
Вес	14,4 кг